



Septentrio mosaic-go is an evaluation kit integrating multi-frequency, multi-constellation receiver module. mosaic-go has been designed for easy evaluation of mosaic-X5 modules into applications like robotics and autonomous systems.

This high-reliability receiver tracks all Global Navigation Satellite System (GNSS) constellations and supports all current and future signals. With Septentrio's unique AIM+ technology for interference mitigation included, Septentrio is now offering a performance benchmark in mass market GNSS positioning.

KEY FEATURES

- ▶ All-in-view satellite tracking: multi-constellation, multi-frequency
- ▶ Best-in-class RTK performance
- ▶ AIM+ unique interference monitoring and mitigation technology
- ▶ Industry-leading ultra-low power consumption
- ▶ Easy-to-use

BENEFITS

No performance compromises

Sized at only 71 x 59 x 12 mm and weighing only 58 g, mosaic-go offers unmatched size to performance ratio.

mosaic-go includes:

- ▶ High update rate (>100 Hz) and low latency, both crucial for control systems of autonomous applications
- ▶ Reliable centimetre-level positioning
- ▶ Full L2 support via P(Y) code

Advanced technologies inside

Septentrio's **GNSS+** toolset enables accuracy and reliability in the toughest conditions, allowing you to complete projects with high quality and efficiency. It includes:

- ▶ **AIM+** the most advanced on-board interference mitigation technology on the market (narrow and wide band, chirp jammers).
- ▶ **LOCK+** for robust tracking during high vibrations and shocks.
- ▶ **APME+** multipath mitigation to disentangle direct signal and those reflected from nearby structures.
- ▶ **IONO+** provides advanced protection against ionospheric disturbances.

FEATURES

GNSS technology

448 hardware channels for simultaneous tracking of all visible supported satellite signals¹:

- ▶ GPS: L1C/A, L1PY, L2C, L2P, L5
- ▶ GLONASS: L1CA, L2CA, L2P, L3 CDMA
- ▶ Beidou: B1I, B1C, B2a, B2I, B3
- ▶ Galileo: E1, E5a, E5b, E5 AltBoc
- ▶ QZSS: L1C/A, L2C, L5
- ▶ Navic: L5
- ▶ SBAS: Egnos, WAAS, GAGAN, MSAS, SDCM (L1, L5)
- ▶ On module L-band

Septentrio's patented GNSS+ technologies

- ▶ **AIM+** interference monitoring and mitigation (narrow band, wide band, chirp jammers)
- ▶ **IONO+** advanced scintillation mitigation
- ▶ **APME+** a posteriori multipath estimator for code and phase multipath mitigation
- ▶ **LOCK+** superior tracking robustness under heavy mechanical shocks or vibrations
- ▶ **RAIM+** receiver autonomous integrity monitoring

5 constellation RTK (base and rover)

Moving base RTK²

Protocols

Septentrio Binary Format (SBF)

NMEA 0183, v2.3, v3.03, V4.0

RINEX v2.x, v3.x

RTCM v2.x, v3.x (MSM included)

CMR v2.0 (out/in), CMR+ (input only)

Interfaces

2 UART (LVTTTL, up to 4 Mbps)

USB device (2.0, HS)

SDIO (mass storage)

1 Event markers¹

1 Configurable PPS out⁸

PERFORMANCE

RTK performance ^{3,4,5}

Horizontal accuracy	0.6 cm + 0.5 ppm
Vertical accuracy	1 cm + 1 ppm
Initialisation time	7 s

Other positioning modes accuracy ^{3,4}

	Horizontal	Vertical
Standalone	1.2 m	1.9 m
SBAS	0.6 m	0.8 m
DGNSS	0.4 m	0.7 m

Velocity accuracy

3 cm/s

Maximum update rate

Position	100 Hz
Measurements only	100 Hz

Latency ⁷

<10 ms

Time precision

xPPS out ⁸	5 ns
Event accuracy	< 20 ns

Time to first fix

Cold start ⁹	< 45 s
Warm start ¹⁰	< 20 s
Re-acquisition	1 s

Tracking performance (C/N0 threshold)

Tracking	20 dB-Hz
Acquisition	33 dB-Hz

Firmware

Free product lifetime upgrades

PHYSICAL AND ENVIRONMENTAL

Package

Size	71 x 59 x 12 mm
Weight	58 g

Electrical

Antenna pre-amplification range	15-50 dB
Antenna bias voltage	3.0-5.5 V
Build-in current limit (150 mA)	
Input voltage	3.3 VDC +/-5%
Power consumption	0.6 W typ 1.1 W max

Environmental

Operating temp	-40 to 85° C -40 to 185° F
Storage temp	-55 to 85° C -67 to 185° F

Humidity	5% - 95% (non-condensing)
----------	---------------------------

Certification	CE, RoHS, WEEE, ISO 9001-2015
---------------	-------------------------------



¹ Configuration dependent
² Output rate 20 Hz
³ Open sky conditions
⁴ RMS levels
⁵ Baseline <40 km
⁶ After convergence
⁷ 99.9%
⁸ Incl. software compensation of sawtooth effect
⁹ No information available (no almanac, no approx position)
¹⁰ Ephemeris and approx. position known



LANDMARK Produktions- und Handelsgesellschaft m.b.H.
 Bahnhofstraße 8b, A-6922 Wolfurt, www.landmark.at,
 info@landmark.at, Telefon + 43 (0) 5574 - 63 54 9,
 Fax: +43 (0) 5574 - 63 63 9
 www.facebook.com/landmark.at/